

1448NC Soft Clean System



The 1448NC Soft Clean System has been specifically developed to meet the needs of the stone cleaning industry, where delicate controlled abrasive cleaning is required.

The system is designed to use the complete range of micro abrasives including: stone grit extrafine, and all other fine aluminium silicates, calcium carbonate, glass bead and grit and speciality media such as dolomite and bi-carbonate of soda.

With an operating pressure as low as 0.5 bar / 8 psi the soft clean offers unlimited cleaning potential.

It is able to tackle delicate tasks such as the cleaning of furniture, domestic woodwork e.g. doors, staircases and window frames, antique vehicles, faced brickwork, plasterboard and delicate stonework.

It is also used for the the cleaning of heavy steelwork and concrete removal.

The soft clean system operates dry, but can be fitted with the wet blast water injection kit to suppress airborne dust.

Built to the same high specifications as all Hodge Clemco machines, the unit has many features to facilitate the needs of the stone cleaning industry.

- Operating pressures of under 0.5 bar can be achieved.
- The system is able to utilise all commonly available nozzles from 2mm to 12.5 mm diameter.
- The unit operates wet or dry (when the wash down facility is incorporated).
- Water consumption is approximately 4 ltr/min.
- Mains water supply is not required.

The machine is supplied in a modular form allowing the selection of the most suitable option for individual requirements.

To ensure maximum working efficiency is achieved, this unit is covered in Hodge Clemco specialist training courses run on site or at Hodge Clemco in Sheffield.