

XHD™ RAC® SwitchTip

High-Pressure Airless Spray Tip



Improve spraying productivity and reduce downtime with the new XHD RAC SwitchTip

- Saves time no screwdriver required
- Change tip sizes in seconds without removing the tip guard housing
- · Locking tab ensures tip stays securely in guard
- For heavy-duty applications up to 7250 psi (500 bar, 50.0 MPa)
- Recommended for Xtreme® Sprayers and XTR™ Airless Spray Guns



Graco XTR Guns

Rugged design to handle the toughest protective coatings

- Compact design
- Lightweight and ergonomic
- XTR-5: 5000 psi (345 bar, 34.5 MPa)
- XTR-7: 7250 psi (500 bar, 50.0 MPa)
- Variety of handle and trigger options



XTR-5 Airless Spray Gun

Maximum working pressure: 5000 psi (345 bar, 34.5 MPa)

XTR500 1-in round handle, four-finger trigger, no tip

XTR501 1-in round handle, four-finger trigger, flat tip*

XTR502 Oval insulated handle, four-finger trigger, XHD RAC tip*

XTR503 Oval insulated handle, two-finger trigger, XHD RAC tip*

XTR504 1-in round handle, four-finger trigger, XHD RAC tip*

XTR505 1-in round handle, two-finger trigger, XHD RAC tip*

XTR-7 Airless Spray Gun

Maximum working pressure: 7250 psi (500 bar, 50.0 MPa)

XTR700 1-in round handle, four-finger trigger, no tip

XTR701 1-in round handle, four-finger trigger, flat tip*

XTR702 Oval insulated handle, four-finger trigger, XHD RAC tip*

XTR703 Oval insulated handle, two-finger trigger, XHD RAC tip*

XTR704 1-in round handle, four-finger trigger, XHD RAC tip*

XTR705 1-in round handle, two-finger trigger, XHD RAC tip*

* Includes 519 tip

Contact us today!

For more information, call **1-877-844-7226** or visit us online at **www.graco.com**

XHD RAC SwitchTip



Genuine Graco quality in a high-pressure tip

ORIFICE SIZE - INCHES

FAN WIDTH	IN	(MM)	.007	.009	.011	.013	.015	.017	.019	.021	.023	.025	.027	.029	.031	.033	.035	.037	.039
	2-4	(51-102)	107	109	111	113	115	117	119	121									139
	4-6	(102-152)		209	211	213	215	217	219	221		225	227	229	231		235		239
	6-8	(152-203)	307	309	311	313	315	317	319	321	323	325	327	329	331	333	335	337	339
	8-10	(203-254)		409	411	413	415	417	419	421	423	425	427	429	431	433	435	437	439
	10-12	(254-305)		509	511	513	515	517	519	521	523	525	527	529	531	533	535	537	539
	12-14	(305-356)		609	611	613	615	617	619	621	623	625	627	629	631	633	635	637	639
	14-16	(356-406)			711	713	715	717	719	721	723	725	727	729	731	733	735	737	739
	16-18	(406-457)				813	815	817	819	821	823	825	827	829	831	833	835	837	839
	18-20	(457-508)									923		927		931	933	935	937	939
		Rate (gpm) Rate (lpm)	.05 .20	.09 .33	.12 .49	.18 .69	.24 .91	.31 1.17	.38 1.47	.47 1.79	.57 2.15	.67 2.54	.74 2.96	.90 3.42	1.03 3.90	1.17 4.42	1.31 4.98	1.47 5.56	1.63 6.18

ORIFICE SIZE - INCHES

IN	(MM)	.041	.043	.045	.047	.049	.051	.053	.055	.057	.059	.061	.063	.065	.067	.069	.071	.075	.081
2-4	(51-102)																		
4-6	(102-152)																		
6-8	(152-203)	341	343	345	347		351		355										
8-10	(203-254)	441	443	445	447	449	451		455		459	461	463	465	467		471	475	481
10-12	(254-305)	541	543	545	547	549	551	553	555	557		561		565	567		571	575	
12-14	(305-356)	641	643	645	647	649	651		655	657	659	661	663	665	667	669	671	675	
14-16	(356-406)	741	743		747	749	751	753	755			761			767		771		
16-18	(406-457)	841	843		847		851		855			861	863		867				
18-20	(457-508)																		1 I
		1.8 6.83	1.98 7.51	2.17 8.23	2.37 8.98	2.58 9.76	2.79 10.57	4.26 16.13	3.25 12.29	3.49 13.20	3.74 14.14	4.0 15.12	4.26 16.13	4.53 17.17	4.82 18.24	5.11 19.34	5.41 20.48	6.04 22.85	7.04 26.66
	2-4 4-6 6-8 8-10 10-12 12-14 14-16 16-18 18-20	2-4 (51-102) 4-6 (102-152) 6-8 (152-203) 8-10 (203-254) 10-12 (254-305) 12-14 (305-356) 14-16 (356-406) 16-18 (406-457)	2-4 (51-102) 4-6 (102-152) 6-8 (152-203) 341 8-10 (203-254) 441 10-12 (254-305) 541 12-14 (305-356) 641 14-16 (356-406) 741 16-18 (406-457) 841 18-20 (457-508) Flow Rate (gpm) 1.8	2-4 (51-102) 4-6 (102-152) 6-8 (152-203) 341 343 8-10 (203-254) 441 443 10-12 (254-305) 541 543 12-14 (305-356) 641 643 14-16 (356-406) 741 743 16-18 (406-457) 841 843 18-20 (457-508) Flow Rate (gpm) 1.8 1.98	2-4 (51-102)	2-4 (51-102)	2-4 (51-102)	2-4 (51-102)	2-4 (51-102)	Color Colo	2-4 (51-102)	2-4 (51-102)	2-4 (51-102)	2-4 (51-102)	Color Colo	2-4 (51-102)	2-4 (51-102)	2-4 (51-102)	2-4 (102-152) 4-6 (102-152)

Water @ 2000 psi (138 bar, 13.8 MPa) - paints with a higher viscosity will decrease the flow rate Example: for a tip with a .039 in orifice and a 10-in (254 mm) pattern, order XHD539

Graco XHD Guard

XHD001 XHD RAC Guard for pressures up to 7250 psi (500 bar, 50.0 MPa)

Flexible design

• Compatible with the original Heavy Duty RAC SwitchTips (GHDxxx)



You can use the new XHD tips in the old GHD guards. Order **247634 Seat and Seal Kit**. (5-pack)



You can use the old GHD tips in the new XHD guards. Order **XHD010 Seat and Seal Kit**. (5-pack)