



Plastic Medias

TECHNICAL DATA

Brand Name: **NyFlash** Mac'Ants Group Ref: **NX or NY**

Product: Polyamide Deflashing Media

Description: Extruded Thermoplastic Nylon / Polyamide Deflashing Media

Application: Polyamide or Nylon based Deflashing Media for use in either manually or automatically operated. Can be used for precision electronic and micro chip manufacture and processing, mould cleaning and delicate component.

Chemical Composition:

Compound	Typical Content %
Polyamide 6 matrix	>99
Anti static additive & pigment	<1

Physical Parameters:

Bulk Density	0.7 g /cc (subject to grade)
Shape	Cubical in form X ; Cylindrical in form Y
Colour	Red - R Natural - N
Specific Gravity	1.15 – 1.23 g/cc
Hardness	3.2 Moh (25-35 Barcol)

Gradation:

0.4mm ; 0.5mm; 0.75mm; 1.00mm; 1.50mm; 2.00mm

Packaging:

Typically 25 kg multi cardboard boxes or 25kg plastic sealed sacks

Compliance:

This product is exempt from registration requirements under REACH.

Page: 2-5-1
Issue: 2
Date: Apr 2011

Document Status: ~~Controlled~~ / **Uncontrolled**

E & OE

Mac'Ants Group, Todwick Road, Dinnington, Sheffield S25 3SE UK
Tel: +44 (0) 1909 552500 Fax : +44 (0) 1909 568726
Email: group@macants.co.uk www.macants.co.uk